



19" Rack Mount  
Power Distribution Unit (PDU)

## HIGHLIGHTS

- 19" Rack Mountable
- 4-Way Rotating Metal Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

## OPTIONS

- Fixed Plastic Mounting Ear Option
- Vertical Rack Mountable
- Socket Number on Demand
- Red/White/Black Color Option
- Cable Length on demand

## THE PACKAGE INCLUDES

- PDU
- Screw & Nut Set for Installation

## DESIGN & MATERIAL

Plastic Material	Fire-retardant - Nylon 6 v0-v2
Body Material	Aluminum Profile Body
Sockets Types	SCHUKO (DIN49440-GERMAN) UPS (DIN49441 - UPS) IEC320 C13 IEC320 C19 UK (BS1363)
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm <sup>2</sup> / 3x2,5 mm <sup>2</sup> / 3x4 mm <sup>2</sup> / 3x6 mm <sup>2</sup> / 5x4 mm <sup>2</sup> / 5x6 mm <sup>2</sup>
Rack Mount	19" 1U veya 2U Rack Mountable Rotatable Metal Mounting Ears
Contacts	Brass
Protection	• Circuit Breaker • Button Fuse • On/Off Switch • Surge Protect • Multimeter • Volt/Amperemeter
Certificate	CE
Warranty	Lifetime (on production based errors)

## ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	UPS PLUG (DIN49441) UK 13A Plug (BS1363) CEE Norm 16A / 32A (EN60309) Plug SCHUKO (DIN 49440) Plug IEC 320 (C14 & C20) Plug
Max. Output power	4000W (220V)
Nominal Input Voltage	100-240V
Max. Total Current Draw	16A
Operable Humidity	% 5-95
Operable Temperature	-5 °C to +45 °C
Storage Temperature	-25 °C to +65 °C



Product Code	Product Name	Box Dimensions
DR-7951-6F	19" 1U 6 Way Schuko 16A Fused PDU w/ 3x1,5mm <sup>2</sup> 1,8mt Cable UPS Plug	5x10x52 cm
DR-7951-9F	19" 2U 9 Way Schuko 16A Fused PDU w/ 3x1,5mm <sup>2</sup> 1,8mt Cable UPS Plug	10x10x52 cm
DR-7951-12F	19" 2U 12 Way Schuko 16A Fused PDU w/ 3x1,5mm <sup>2</sup> 1,8mt Cable UPS Plug	10x10x52 cm



