



ZeroU Single Phase Vertical Alm. 20x13 Locked 4x19 Locked Socket with 2x16A Circuit Breaker  
3 m. 3x6 mm<sup>2</sup> Power Cable and 32A CEE Norm Plug Locally Metered PDU

## HIGHLIGHTS

- Vertical Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

## YOU CAN LOCALLY METER

- Volt
- Amper
- Watt
- Environment Temperature
- Power Factor
- Total Operating Time
- Kw for operating time

## THE PACKAGE INCLUDES

- PDU
- Screw & Nut Set for installation

## DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	2x10 Locked IEC 320 C13 2x2 Locked IEC 320 C19
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / <b>3 Mtr</b> / 5 Mtr 3x2,5 mm <sup>2</sup> /3x4 mm <sup>2</sup> / 3x6 mm <sup>2</sup> / 5x2,5 mm <sup>2</sup> / <b>3x6mm<sup>2</sup></b>
Rack Mount	Vertical Rack Mountable
Contacts	Brass
Protection	<b>2x16A Circuit Breaker, Multimeter Screen</b> On/Off Switch Surge Protect Voltmeter
Certificate	CE
Warranty	Lifetime (On Production Based Errors)

## ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	<b>CEE NORM 32A (EN60309)</b> IEC 320 C20 UPS (DIN49441) UK 13A (BS1363)
Max. Output power	7000W -Single Phase
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	32A
Operable Humidity	% 5-95
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65°C



